

Model detail

CC17B

LX 17 SEER
R-410A
Split System
Air Conditioner
Coleman

Product Line:
LX Residential

Capacity
Nominal Capacity:
2 - 5 Tons

Warranty
Parts:
5-Years Limited

Application
Residential

Product Benefits

- **Superior Coil Protection** – An easily removable two-piece steel extruded louver coil guard protects the tube-in-fin coil from debris and physical damage while making access for coil cleaning quick and simple.
- **Environmentally Friendly Refrigerant** – The next generation refrigerant R-410A delivers environmentally friendly performance with zero ozone depletion.
- **Durable Finish** – A high quality powder paint finish rated at 1000 hrs. salt spray provides the ultimate protection from corrosion and harmful UV rays, ensuring a long-lasting, high quality appearance.
- **ECM Fan Motor** – Dynamically adjusts speed in sync with the compressor stage to keep heat exchange in balance while minimizing power consumption and sound.
- **Swept Wing Fan** – A design adapted from aerospace engineering provides whisper-quiet operation by allowing air to flow smoothly and efficiently across the fan surface and edges.
- **High-Efficiency Outdoor Coil** – An aluminum fin and copper tube outdoor coil provide easy cleaning, low restriction to airflow and efficient heat exchange.
- **Factory Installed Filter-Drier** – A corrosion resistant copper, solid core liquid line filter-drier removes debris and moisture which can be harmful to the system.
- **Easy Service Access** – A large electrical box cover and a swing open electrical box provide superior full corner access to the inside of the unit for maintenance or service.
- **TXV Controls** – All indoor coils, whether in the cased CF/CM coil or in an air handler, utilize dealer installed TXVs (Thermostatic Expansion Valves).
- **Conventional Controls** – Designed to operate as a conventionally wired system for ease of installation and reliable operation.
- **Two Speed, Protected Scroll Compressor** – The compressor is solenoid operated for 67% and 100% capacity. A suction accumulator tank, on 3, 4 & 5 ton models, protects the compressor from harm.
- **Standard System Warranty*** - 10-Years Limited compressor/10-Years Limited parts/90-Days Limited labor warranty when registered online within 90 days of installation.
- **Agency Listed** - Safety certified by CSA to UL 1995 / CSA 22.2. Performance certified to ANSI/AHRI Standard 210/240 in accordance with the Unitary Small Equipment certification program.

*Must be registered online within 90 days of installation to qualify for the 10-Years parts / 10-Years compressor limited warranty. Otherwise, the warranty reverts to the standard 5-Years parts / 10-Years compressor limited warranty as published in the product warranty certificate. This warranty does not apply to R-22 models, 3-Phase models, or internet sales. See the Limited Warranty certificate in the User's Information Manual for details.

Verify the actual ratings for each specific matchup in the online AHRI directory at www.ahridirectory.org at the time of sale. It is also recommended to print the rating certificate, if needed, at the time of sale.